

LED Display Screen

VTAC LED's Display screen series perfectly designed for the best video output and display of images and information. Offering Display color of 281 trillions(synchronized). The perfect product for advertising and marketing.



Product Features

- Powerful LED display screen available in Indoor and Outdoor series
- Displays digital content such as Video, Images & Information
- Good Brand Value addition for Advertising
- Easy Installation

Applications

Suitable for Outdoor and Indoor Advertising, Hotel conference room, Restaurants, Showrooms, Casinos, Government facilities, Theaters, Retail outlets, Traffic control room, Security monitoring room, Stage background, HD cinema, Shopping malls, Railway stations, Airports.



Indoor Display Screen

P5 Indoor LED Finished Cabinet

SKU **11077** EAN Code **3800157617468** **A++**

BOX QTY.
06



Screen Parameter

Pixel Density	40000dots/sqm
Brightness	1800nits
Optimum View Distance	more than 5m
Gray Scale	16bits
Display Color	281 trillions(synchronized)
Operation Power	220V-240V
Max Power Consumption	750W/sqm
Control Mode	Synchronized
Refresh Frequency	400-700HZ
Fram Frequency	60HZ
Surport Signal Input	S-Video,RGBHV,YUV etc.
Control Distance	UTP140M,SINGLE MODE FIBER 15KM
Life Span(50% Brightness)	100000hrs
IP(Front/rear)	IP20

LED Cabinet Parameter

Cabinet Size(L*h*d)	640*640mm
Cabinet Resolution	128*128
Module Quantity Each Cabinet	2*4=8
Average Power Consumption	300w/cabinet
Cabinet Material	Iron
Cabinet Size	8kg/cabinet

LED Module Parameter

Pixel Pitch	5mm
Led Specification	SMD3528
Led Configuration	SMD 3 in 1
Module Size	320*160mm
Module Resolution	64*32=2048dot
Drive Method	1/16 scan constant current
Drive IC	SM16106



Indoor Display Screen

P4 Indoor LED Display Screen

SKU **11079** EAN Code **3800157619493**



BOX QTY.
06



Plug & Play



Ideal For Renting Purpose



Portable Moving For Events

Screen Parameter

Pixel Density	62500dots/sqm
Brightness	1100nits
Optimum View Distance	more than 5m
Gray Scale	16bits
Display Color	281 trillions(synchronized)
Operation Power	AC 220V-240V/ 50/60Hz
Power Consumption	300W/cabinet
Control Mode	Synchronized
Refresh Frequency	400-700HZ
Surport Signal Input	S-Video,RGBHV,YUV etc.
Control Distance	UTP140M,SINGLE MODE FIBER 15KM
Life Span(50% Brightness)	100000hrs
IP(Front)	IP40
Control System	PCTV nonlinearity card, DVI display card Linsn control system

LED Cabinet Parameter

Cabinet Size(L*h*d)	512*512*85mm
Cabinet Resolution	128*128
Module Quantity Each Cabinet	2*4=8
Power Consumption	300w/cabinet
Cabinet Material	Iron
Cabinet Weight	8kg/cabinet

LED Module Parameter

Pixel Pitch	4mm
Led Specification	SMD2121
Led Configuration	SMD 3 in 1
Module Size	256*128mm
Module Resolution	64*32=2048dot
Drive Method	1/16 scan constant current
Drive IC	SM16106
Power Consumption	25-30W

Windows 10



DUAL DISPLAY TOUCH SCREEN



Media Player SKU **11088** EAN Code **3800157622820** **BOX QTY.** **04**

Features:

- | | |
|---|---|
| <input checked="" type="checkbox"/> LED Display Player with Industrial PC | <input checked="" type="checkbox"/> Input - AC:120-260V |
| <input checked="" type="checkbox"/> One TS802 sending card inside | <input checked="" type="checkbox"/> 1 x Audio In |
| <input checked="" type="checkbox"/> Dual Display - Supports Max 1280*800 | <input checked="" type="checkbox"/> 1 x Audio Out |
| <input checked="" type="checkbox"/> Supports SD Memory Card/USB/HDMI Out/Internet | <input checked="" type="checkbox"/> 1 x DVI In |
| <input checked="" type="checkbox"/> USB and SD Card Memory Playing | <input checked="" type="checkbox"/> 1 x HDMI Out |
| <input checked="" type="checkbox"/> Compact and Easy to Install | <input checked="" type="checkbox"/> 4 USB Interface |
| <input checked="" type="checkbox"/> 7" Touch Screen with windows 10 Inside | |
| <input checked="" type="checkbox"/> Size - 320*180*50mm | |

Accessories:



Sending Box **BOX QTY.** **20**
SKU **500082**



Sending Card 802 **BOX QTY.** **20**
SKU **500081**